

DESOTO, INC.
MATERIAL SAFETY DATA SHEET

NPCA 1-72

FOR COATINGS, RESINS, AND RELATED MATERIALS

(APPROVED BY US DEPARTMENT OF LABOR "ESSENTIALLY SIMILAR" TO FORM OSHA-20)
SECTION I

DESOTO, INC.
ADMINISTRATIVE AND RESEARCH CENTER

1700 S. MT. PROSPECT ROAD
DES PLAINES, ILLINOIS 60018

EMERGENCY TELEPHONE (312) 391-9000

PRODUCT CLASS

SOLVENT

MANUFACTURERS CODE IDENTIFICATION
020-730

TRADE NAME

SUPER DESOTHAINE
SUPERSEDES 01/25/82 MSDS

DATE OF PREPARATION 08/23/82

DPN 5372-1
***** SECTION II-HAZARDOUS INGREDIENTS *****

INGREDIENT	% BY* WEIGHT	PPM	TLV	MG/CU.M	LEL	VAPOR PRESSURE @ 20 DEG C
METHYL ETHYL KETONE	30.0	200		590	1.8	70
ETHYL ACETATE	35.0	400		1400	2.2	76
2-ETHOXYETHYL ACETATE-SKIN **	35.0	50		270	1.8	2.0

* PERCENT BY WEIGHT:

TO NEAREST 5%, PLUS OR MINUS 5%, FOR SUBSTANCES 5-95%;
<5.0 FOR SUBSTANCES 0.5-5.0%;
<0.5 FOR SUBSTANCES 0.0-0.5%.

** ACGIH NOTICE OF INTENDED CHANGE, 1982: TLV-TWA=5PPM

NE = NOT ESTABLISHED
NA = NOT APPLICABLE

***** SECTION III-PHYSICAL DATA *****

PROPERTY	MEASUREMENT
BOILING RANGE	171.0 TO 313.0 DEG F. 77.0 TO 156.0 DEG C. 2760 MM HG
VAPOR DENSITY	X HEAVIER LIGHTER THAN AIR
WEIGHT PER GALLON	7.4 LBS.
PERCENT VOLATILE BY VOLUME	100.0
EVAPORATION RATE	FASTER X SLOWER THAN ETHER

08/23/82

***** SECTION IV-FIRE AND EXPLOSION DATA *****

DOT CATEGORY	FLAMMABLE LIQUID	FLASH POINT	22.0 DEG F.
OSHA CATEGORY	FLAMMABLE LIQUID-CLASS I B	(CLOSED CUP)	-5.6 DEG C.

LOWER EXPLOSIVE LIMIT SEE II

EXTINGUISHING MEDIA: USE NATIONAL FIRE PROTECTION ASSOCIATION CLASS B
EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).

UNUSUAL FIRE AND EXPLOSION HAZARDS: KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES. SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTO IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN.

***** SECTION V-HEALTH HAZARD DATA *****

THRESHOLD LIMIT VALUE: SEE II (NOT ESTABLISHED FOR PRODUCT)

EFFECTS OF OVEREXPOSURE:

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA.

SKIN OR EYE CONTACT: PRIMARY IRRITATION.

OTHER HEALTH EFFECTS:

REPRODUCTIVE AND BLOOD DISORDERS AND BIRTH DEFECTS HAVE BEEN OBSERVED IN TESTS ON LABORATORY ANIMALS WITH 2-METHOXYETHANOL, 2-ETHOXYETHANOL, AND 2-ETHOXYETHYL ACETATE. BECAUSE THIS PRODUCT CONTAINS AT LEAST ONE OF THESE SOLVENTS, HANDLING PRECAUTIONS AS OUTLINED IN SECTIONS VIII AND IX SHOULD BE CAREFULLY FOLLOWED TO AVOID OVEREXPOSURE.

EMERGENCY AND FIRST AID PROCEDURES: INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM AND QUIET. NOTIFY A PHYSICIAN. SKIN CONTACT: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYSICIAN. EYE CONTACT: FLUSH WITH WATER FOR 15 MINUTES. CONSULT A PHYSICIAN.

INGESTION: CONSULT A PHYSICIAN.

***** SECTION VI-REACTIVITY DATA *****

STABILITY: UNSTABLE X STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

HAZARDOUS DECOMPOSITION PRODUCTS:
PRODUCTS OF COMBUSTION ARE HAZARDOUS

HAZARDOUS POLYMERIZATION:	MAY OCCUR	X WILL NOT OCCUR
---------------------------	-----------	------------------

CONDITIONS TO AVOID:

08/23/82

***** SECTION VII-SPILL OR LEAK PROCEDURES*****

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

WASTE DISPOSAL METHODS: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

*****SECTION VIII-SPECIAL PROTECTION INFORMATION *****

RESPIRATORY PROTECTION:

IF EXPOSURE EXCEEDS OCCUPATIONAL EXPOSURE LIMITS INDICATED IN SECTION 11 USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. IN CONFINED AREAS USE "NIOSH" APPROVED AIR LINE TYPE RESPIRATORS OR HOODS.

VENTILATION: WHERE EMPLOYEES MAY BE EXPOSED, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS IN SECTION II BELOW RECOMMENDED ("ACGIH") OR REGULATED ("OSHA") LIMIT. WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEL IN SECTION II BELOW 25% OF LIMIT

PROTECTIVE GLOVES: BUTYL RUBBER PREFERRED. NEOPRENE OR NITRILE ACCEPTABLE.

EYE PROTECTION: SPLASH PROOF GOGGLES AND/OR FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT:

PROTECTIVE CLOTHING SUCH AS BUTYL RUBBER APRON. NEOPRENE OR NITRILE ACCEPTABLE. A SAFETY SHOWER, AN EYE BATH, AND WASHING FACILITIES SHOULD BE AVAILABLE.

***** SECTION IX-SPECIAL PRECAUTIONS *****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF FLAMMABLE LIQUIDS.

OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY. CONTAMINATED CLOTHING SHOULD BE WASHED BEFORE REUSE. CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

DO NOT SAND, FLAME CUT, BRAZE OR WELD THE DRY COATING WITHOUT "NIOSH" APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

OBSERVE PRECAUTIONARY LABEL WARNINGS.

PREPARED BY: R. A. PROKOP